

AGM READY
MÁXIMA POTENCIA Y DURABILIDAD

LISTA PARA USAR



FICHA TÉCNICA

Referencia	Voltaje	Capacidad (Ah)	Intensidad de arranque (CCA)	Polaridad	Terminales	Talón de sujeción	Longitud	Ancho	Altura
AGM12-4	12V	3	50	1	M04	B0	115	70	85
AGM12-5	12V	4	70	0	M04	B0	115	70	105
AGM12-7F	12V	7	85	3	Faston S (4,8)	B0	150	65	95
AGM12-8	12V	8.6	145	1	M12	B0	150	87	95
AGM12-9	12V	9	120	1	M04	B0	135	75	140
AGM12-10	12V	10	150	1	M04	B0	150	90	130
AGM12-12M	12V	12	200	1	M04	B0	150	90	145
AGM12-12	12V	12	200	1	M04	B0	150	90	145
AGM12-16	12V	16	170	1	M04	B0	150	90	160
AGM12-12F	12V	12	150	3	Faston S (4,8)	B0	150	100	100
AGM12-14	12V	12	210	0	M04	B0	135	90	165
AGM12-18	12V	18	250	0	M11	B0	180	75	165
AGM12-23	12V	21	350	0	M04	B0	205	90	165
AGM12-31	12V	30	430	0	M04	B0	165	130	175
GEL12-14	12V	14(20h)	150	1	Female M6	B0	150	90	145
GEL12-16	12V	16 (20h)	100	0	M11	B0	180	75	165
GEL12-19	12V	19 (20h)	170	0	M11	B0	185	80	170
GEL12-30	12V	30 (20h)	180	1	EN	B0	197	132	186

TUDOR®
B A T T E R I E S