



AGM
LA BATERÍA DE
ALTAS PRESTACIONES

FICHA TÉCNICA

| Referencia | Voltaje | Capacidad (Ah) | Intensidad de arranque (CCA) | Polaridad | Terminales | Talón de sujeción | Longitud | Ancho | Altura |
|-------------|---------|----------------|------------------------------|-----------|------------|-------------------|----------|-------|--------|
| ET4B-BS | 12V | 2,3 | 35 | 4 | M13 | B0 | 115 | 40 | 85 |
| ETR4A-BS | 12V | 2.3 | 35 | 4 | M14 | B0 | 115 | 50 | 85 |
| ETX4L-BS | 12V | 3 | 50 | 0 | M04 | B0 | 115 | 70 | 85 |
| ETX5L-BS | 12V | 4 | 70 | 0 | M04 | B0 | 115 | 70 | 105 |
| ETX7A-BS | 12V | 6 | 90 | 1 | M04 | B0 | 150 | 90 | 95 |
| ETX7L-BS | 12V | 6 | 100 | 0 | M04 | B0 | 115 | 70 | 130 |
| ETZ7-BS | 12V | 6 | 100 | 0 | M04 | B0 | 115 | 70 | 105 |
| ET7B-BS | 12V | 6,5 | 85 | 1 | M04 | B0 | 150 | 65 | 95 |
| ET9B-BS | 12V | 8 | 110 | 1 | M04 | B0 | 150 | 70 | 105 |
| ETX9-BS | 12V | 8 | 120 | 1 | M04 | B0 | 150 | 90 | 105 |
| ETZ10-BS | 12V | 8.6 | 145 | 1 | M04 | B0 | 150 | 90 | 95 |
| ETX9C-BS | 12V | 9 | 120 | 1 | M04 | B0 | 135 | 75 | 139 |
| ET12A-BS | 12V | 9.5 | 130 | 1 | M04 | B0 | 150 | 90 | 105 |
| ET12B-BS | 12V | 10 | 160 | 1 | M04 | B0 | 150 | 70 | 130 |
| ETX12-BS | 12V | 10 | 150 | 1 | M04 | B0 | 150 | 90 | 130 |
| ETZ14-BS | 12V | 11.2 | 205 | 1 | M04 | B0 | 150 | 87 | 110 |
| ET14B-BS | 12V | 12 | 190 | 1 | M04 | B0 | 150 | 70 | 145 |
| ETX14-BS | 12V | 12 | 200 | 1 | M04 | B0 | 150 | 90 | 145 |
| ETX14AH-BS | 12V | 12 | 210 | 1 | M04 | B0 | 135 | 90 | 165 |
| ETX14AHL-BS | 12V | 12 | 210 | 0 | M04 | B0 | 135 | 90 | 165 |
| ETX14L-BS | 12V | 12 | 200 | 0 | M04 | B0 | 150 | 90 | 145 |
| ETX16-BS | 12V | 14 | 215 | 1 | M04 | B0 | 150 | 90 | 160 |
| ETX20CH-BS | 12V | 18 | 230 | 1 | M04 | B0 | 150 | 90 | 160 |
| ETX20HL-BS | 12V | 18 | 270 | 0 | M04 | B0 | 175 | 87 | 155 |
| ETX20H-BS | 12V | 18 | 270 | 1 | M04 | B0 | 175 | 87 | 155 |
| ETX24HL-BS | 12V | 21 | 350 | 0 | M04 | B0 | 205 | 90 | 165 |

TUDOR[®]
B A T T E R I E S